

HANSA-FLEX OEL HVLPD 46

Revision date: 27.11.2020

Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking
1.1. Product identifier

HANSA-FLEX OEL HVLPD 46

1.2. Relevant identified uses of the substance or mixture and uses advised against
Use of the substance/mixture

Hydraulic oil.

Product Categories [PC]: PC 17 Hydraulic fluids.

1.3. Details of the supplier of the safety data sheet

Company name: HANSA-FLEX AG

Street: Zum Panrepel 44

Place: D-28307 Bremen

Telephone: +49 (0) 421 48907 0

Telefax: +49 (0) 421 48907 48

e-mail: info@hansa-flex.com

Internet: www.hansa-flex.de

1.4. Emergency telephone

+49 (0) 551-19240

number:

Giftinformationszentrum NORD GIZ-NORD

SECTION 2: Hazards identification
2.1. Classification of the substance or mixture
Regulation (EC) No. 1272/2008

This mixture is not classified as hazardous in accordance with Regulation (EC) No. 1272/2008.

2.2. Label elements
Regulation (EC) No. 1272/2008
Special labelling of certain mixtures

EUH208 Contains Benzenesulfonic acid, mono-C15-36-branched alkyl derivs., calcium salts. May produce an allergic reaction.

EUH210 Safety data sheet available on request.

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

Do not handle until all safety precautions have been read and understood.

Discharge into the environment must be avoided.

SECTION 3: Composition/information on ingredients
3.2. Mixtures
Chemical characterization

Contains: Mineral oil, Additive.

Further Information

The mineral oils in the product contain < 3 % DMSO-extract (IP 346).

SECTION 4: First aid measures
4.1. Description of first aid measures
General information

First aider: Pay attention to self-protection!

Move victim out of danger zone.

Remove contaminated, saturated clothing immediately.

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

HANSA-FLEX OEL HVLPD 46

Revision date: 27.11.2020

Page 2 of 8

After inhalation

Avoid oil mist
Move victim to fresh air. Put victim at rest and keep warm.
Get medical advice/attention if you feel unwell.

After contact with skin

After contact with skin, wash immediately with: Water and soap.
Immediately remove any contaminated clothing, shoes or stockings.
In case of skin irritation, seek medical treatment.

After contact with eyes

Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing.
In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).
Do NOT induce vomiting. Call a physician immediately.
No administration in cases of unconsciousness or cramps.

4.2. Most important symptoms and effects, both acute and delayed

No information available.
In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Foam, Extinguishing powder, Sand, Water mist, Carbon dioxide (CO₂).

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon dioxide (CO₂), Sulphur dioxide (SO₂), Phosphorus oxides, Carbon monoxide.

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes.
In case of fire: Wear self-contained breathing apparatus.

Additional information

Move undamaged containers from immediate hazard area if it can be done safely.
Use water spray jet to protect personnel and to cool endangered containers. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Provide adequate ventilation.
Respiratory protection necessary at: aerosol or mist generation. (See section 8.)
Avoid contact with skin and eyes. Wear personal protection equipment.
In case of leakage, eliminate all ignition sources. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.
Do not allow to enter into soil/subsoil.

HANSA-FLEX OEL HVLPD 46

Revision date: 27.11.2020

Page 3 of 8

6.3. Methods and material for containment and cleaning up

- Prevent spread over a wide area (e.g. by containment or oil barriers).
- Take up mechanically, placing in appropriate containers for disposal.
- Remove from the water surface (e.g. skimming, sucking).
- High slip hazard because of leaking or spilled product.
- Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).
- Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

- Personal protection equipment: refer to chapter 8.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

- Do not breathe vapour/aerosol. Provide adequate ventilation.
- Avoid contact with skin and eyes. Remove contaminated, saturated clothing immediately.
- For industrial purposes only.

Advice on protection against fire and explosion

- No special fire protection measures are necessary.
- Avoid oil mist
- When hot, product develops flammable vapours.
- Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- Fire class B (DIN EN 2).

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

- Only use containers specifically approved for the substance/product.
- Keep container tightly closed and in a well-ventilated place.
- Always close containers tightly after the removal of product.
- Recommended storage temperature: 5 - 30 °C. Do not store at temperatures over: 40 °C

Hints on joint storage

- Do not store together with: Oxidising agent,
- Keep away from food, drink and animal feedingstuffs.

Further information on storage conditions

- Protect against: Heat, Light, moisture.
- Protect against direct sunlight.

7.3. Specific end use(s)

- Hydraulic oil.
- Observe technical data sheet.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Additional advice on limit values**

- Air limit values: Mineral oil mist
- Limit value type (country of origin): US-OSHA PEL-Value: 5 mg/m³
- Limit value type (country of origin): ACGIH STEL-Value: 10 mg/m³

8.2. Exposure controls**Protective and hygiene measures**

- Do not eat, drink, smoke or sneeze at the workplace.
- Avoid contact with skin, eyes and clothes.
- Protect skin by using skin protective cream.

HANSA-FLEX OEL HVLPD 46

Revision date: 27.11.2020

Page 4 of 8

Take off contaminated clothing and wash it before reuse.
 Wash hands before breaks and after work.
 After cleaning apply high-fat content skin care cream.
 Do not put any product-impregnated cleaning rags into your trouser pockets.

Eye/face protection

Suitable eye protection: Tightly sealed safety glasses. (DIN EN 166)
 In case of increasing hazard add: Eye-shade.

Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): DIN EN 420, EN ISO 374.
 Suitable material: NBR (Nitrile rubber), PVC (polyvinyl chloride), FKM (fluororubber).
 Required properties: liquid-tight.
 penetration time (maximum wearing period): > 240 min.
 Thickness of glove material: 0,4 mm
 Before using check leak tightness / impermeability.

Skin protection

Handling larger quantities: Wear suitable protective clothing.

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.
 Respiratory protection necessary at: exceeding exposure limit values, insufficient ventilation, aerosol or mist generation.
 Suitable respiratory protective equipment: A2, A2/P2 Combination filter device (DIN EN 141)..

SECTION 9: Physical and chemical properties
9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	light yellow - yellow
Odour:	like: mineral oil.

Test method

pH-Value:	not applicable
-----------	----------------

Changes in the physical state

Melting point:	No data available.
Initial boiling point and boiling range:	> 320 °C
Pour point:	< -30 °C DIN ISO 3016
Flash point:	> 220 °C DIN ISO 2592
Lower explosion limits:	approx. 0,6 vol. %
Upper explosion limits:	approx. 6,5 vol. %
Ignition temperature:	> 250 °C DIN 51794

Oxidizing properties

No data available.

Vapour pressure: (at 20 °C)	< 0,1 hPa
Density (at 15 °C):	approx. 0,85 - 0,87 g/cm ³ DIN 51757
Water solubility:	practically insoluble
Viscosity / kinematic: (at 40 °C)	approx. 46 mm ² /s DIN 51562

9.2. Other information

none

SECTION 10: Stability and reactivity**10.1. Reactivity**

No risks worthy of mention.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.
Decomposition takes place from temperatures above: 150 °C

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.
Do not mix with: Oxidizing agents, strong.

10.4. Conditions to avoid

storage stability: Do not store at temperatures over: 40 °C
This material is combustible, but will not ignite readily.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

10.5. Incompatible materials

Oxidizing agents, strong.

10.6. Hazardous decomposition products

Thermal decomposition can lead to the escape of irritating gases and vapours.
In case of fire may be liberated: Carbon dioxide (CO₂), Sulphur dioxide (SO₂), Phosphorus oxides, Carbon monoxide.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity**

Based on available data, the classification criteria are not met.
Based on available data, the classification criteria are not met.

Irritation and corrosivity

Based on available data, the classification criteria are not met.
Irritant effect on the skin: On short hand contact: Not an irritant.
Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).
Irritant effect on the eye: slightly irritant but not relevant for classification.

Sensitising effects

Contains Benzenesulfonic acid, mono-C15-36-branched alkyl derivs., calcium salts. May produce an allergic reaction.
Contains Benzenesulfonic acid, mono-C15-36-branched alkyl derivs., calcium salts: May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.
Based on available data, the classification criteria are not met.
The mineral oils in the product contain < 3 % DMSO-extract (IP 346).

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.
Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

Aspiration hazard

Based on available data, the classification criteria are not met.
Based on available data, the classification criteria are not met.

SECTION 12: Ecological information**12.1. Toxicity**

No information available.

12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria).

12.3. Bioaccumulative potential

No information available.

12.4. Mobility in soil

State of matter: liquid at room temperature.

If product enters soil, it will be mobile and may contaminate groundwater

12.5. Results of PBT and vPvB assessment

PBT: not applicable.

vPvB: not applicable.

12.6. Other adverse effects

No information available.

Further information

Discharge into the environment must be avoided.

Do not allow to enter into surface water or drains.

Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to "Kreislaufwirtschafts- und Abfallgesetz (KrW-/AbfG)". Dispose of waste according to applicable legislation.

The waste key according to the European Waste Catalogue (EWC number) refers to the real wastes origin and therefore is not product- but use-oriented.

Consult the local waste disposal expert about waste disposal.

Observe mixture permissions according to "Altölverordnung (Waste oil directive)".

List of Wastes Code - residues/unused products

130110 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste hydraulic oils; mineral based non-chlorinated hydraulic oils; hazardous waste

List of Wastes Code - used product

130110 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste hydraulic oils; mineral based non-chlorinated hydraulic oils; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Packing which cannot be properly cleaned must be disposed of.

SECTION 14: Transport information**Land transport (ADR/RID)**

HANSA-FLEX OEL HVLPD 46

Revision date: 27.11.2020

Page 7 of 8

14.1. UN number: not relevant**14.2. UN proper shipping name:** not relevant**14.3. Transport hazard class(es):** not relevant**14.4. Packing group:** not relevant**Other applicable information (land transport)**

No dangerous good in sense of these transport regulations.

Inland waterways transport (ADN)**Other applicable information (inland waterways transport)**

No information available.

Marine transport (IMDG)**Other applicable information (marine transport)**

No dangerous good in sense of these transport regulations.

Air transport (ICAO-TI/IATA-DGR)**Other applicable information (air transport)**

No dangerous good in sense of these transport regulations.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Handling (Transport information): No special precautionary measures are necessary. See protective measures under point 7 and 8.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No information available.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information****Additional information**

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH).

National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

Additional information

Restricted to professional users.

The receiver of our product is singularly responsible for adhering to existing laws and regulations. Observe in addition any national regulations!

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 2,3,11.

Relevant H and EUH statements (number and full text)

EUH208 Contains Benzenesulfonic acid, mono-C15-36-branched alkyl derivs., calcium salts. May produce an allergic reaction.

EUH210 Safety data sheet available on request.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

HANSA-FLEX OEL HVLPD 46

Revision date: 27.11.2020

Page 8 of 8

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)